

#### GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (400-470 MHz) Models
- Meets ETSI EN Standards
- 260 CH-GID / 128 Zones (LCD Models)
- 64 CH-GID / 4 Zones (Non LCD Models)
- 12-Key Keypad Models
- 8 Character Alphanumeric Aliases
- Backlit LCD & Keys
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- On / Off Volume Knob
- 16-Position Mechanical Selector
- 4 Front PF Keys (LCD Models)
- 3 Side PF Keys
- Emergency / AUX Key
- Built-in Motion Sensor
- 500 mW Speaker Audio
- Zone / CH Number Voice Announcement
- KMC-48GPS Speaker Mic Option
- KPG-141D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input\*<sup>1</sup>
- Transparent Data Mode\*<sup>1</sup>

#### DIGITAL – GENERAL

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging\*<sup>1 2</sup>
- Remote Stun / Kill\*<sup>1</sup>
- Remote Check\*<sup>1</sup>
- Short & Long Data Messages\*<sup>1</sup>
- GPS Location with Voice\*<sup>1</sup>
- NXDN® Scrambler Included

#### DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call\*<sup>3</sup>
- Mixed FM / Digital Operation
- Conventional IP Networks
- Site Roaming

#### DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Telephone Interconnect
- Transmission Trunked Mode\*<sup>4</sup>
- Message Trunked Mode\*<sup>4</sup>
- Call Queuing with Priority\*<sup>4</sup>
- Late Entry (UID & GID)\*<sup>4</sup>
- 4 Priority Monitor ID's\*<sup>4</sup>
- Remote Group Add\*<sup>1</sup>
- Failsoft Mode

#### MULTI-SITE IP NETWORKS COMPATIBLE

- 60,000 GIDs / UIDs
- Wide Area Group Call
- Auto Roaming Registration
- Group Registration

#### SCAN

- Single Zone / Multi-Zone / List Scan
- Single Priority Scan (Conventional)

#### FM Modes - GENERAL

- 25, 20 & 12.5 kHz Channels
- Conventional & LTR® Zones
- FleetSync® II, MDC-1200, DTMF\*<sup>3</sup>
- QT / DQT & 2-Tone (Conventional Zones Only)\*<sup>3</sup>
- 5-Tone Encode / Decode (Conventional Zones Only)\*<sup>3</sup>
- Voice Inversion Scrambler (16 Codes)

#### dPMR

- Kenwood NEXEDGE® mid tier digital two-way radios can now be adapted to operate as dPMR radios

#### MPT Zones\*

- Single-Site Trunking
- Multi-Site Network Trunking
- 8 Network Capacity
- Network Roaming / Registration

#### FleetSync®/II (FM)

- PTT ID ANI / Caller ID\*<sup>3</sup>
- Selective / Group Call\*<sup>3</sup>
- Emergency, Status & Text Messages\*<sup>1</sup>

#### MDC-1200

- PTT ID ANI / Caller ID\*<sup>3</sup>
- Emergency, Radio Check & Inhibit

\* Optional feature

\*<sup>1</sup> Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

\*<sup>2</sup> Non LCD Models - Pre-programmed key operation.

\*<sup>3</sup> Non LCD Models - Some screen / key-based functions are not available.

\*<sup>4</sup> These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.



NX-220E2/320E2

NX-220E3/320E3

NX-220E/320E

## Options

|   |   |   |   |
|---|---|---|---|
| <ul style="list-style-type: none"> <li><b>KNB-55L</b><br/>Li-ion Battery Pack (1,480mAh)</li> <li><b>KNB-56N</b><br/>Ni-MH Battery Pack (1,400mAh)</li> <li><b>KNB-57L</b><br/>Li-ion Battery Pack (2,000mAh)</li> <li><b>KBP-5</b><br/>6 AA Alkaline Battery Case</li> <li><b>KSC-25</b><br/>Rapid Charger</li> <li><b>KSC-30</b><br/>Regular Charger for Ni-MH Batteries</li> </ul> | <ul style="list-style-type: none"> <li><b>KSC-256</b><br/>Rapid Rate 6-Unit Charger</li> <li><b>KMC-45</b><br/>Speaker Microphone</li> <li><b>KMC-21</b><br/>Speaker Microphone</li> <li><b>KMC-48GPS</b><br/>GPS Speaker Microphone</li> <li><b>KRA-22/23</b><br/>VHF/UHF Whip Antenna</li> <li><b>KRA-26/27</b><br/>VHF Helical/UHF Whip Antenna</li> </ul> | <ul style="list-style-type: none"> <li><b>KMB-30</b><br/>Wall Mount Bracket for KSC-256</li> <li><b>KEP-2</b><br/>Earphone Kit for KMC-45 (2.5mm plug)</li> <li><b>KHS-7/7A</b><br/>Single Muff Headset</li> <li><b>KHS-8BL</b><br/>2-wire Palm Mic w/Earphone</li> <li><b>KHS-9BL</b><br/>3-wire Lapel Mic with Earphone (Black)</li> <li><b>KHS-10-OH</b><br/>Heavy-Duty Noise Reduction Headset</li> </ul> | <ul style="list-style-type: none"> <li><b>KHS-21</b><br/>Headset w/Boom Mic &amp; PTT</li> <li><b>KHS-22</b><br/>Headset w/Boom Mic &amp; PTT</li> <li><b>KHS-29F</b><br/>Clip Mic, w/Earhanger</li> <li><b>EMC-12W</b><br/>Clip Mic w/Earphone &amp; PTT (VOX Ready)</li> <li><b>KBH-12</b><br/>Belt Clip</li> <li><b>KWR-1</b><br/>Water Resistant Bag</li> </ul> |
|---|---|---|---|

## Main Specifications

All accessories and options may not be available in all markets. Contact an authorised Kenwood dealer for details and complete list of all accessories and options.

|  |                    | NX-220  | NX-320      |
|--|--------------------|---|-------------|
| <b>GENERAL</b>   |                    |   |             |
| Frequency Range  |                    | 136-174 MHz   | 400-470 MHz |
| Number of Channels   | LCD Models         | 260 ch  |             |
|  | Non LCD Models     | 64 ch   |             |
| Zones  | LCD Models         | 128 zone  |             |
|  | Non LCD Models     | 4 zone  |             |
| Max. Channels per Zone   | LCD Models         | 250 ch  |             |
|  | Non LCD Models     | 16 ch   |             |
| Channel Spacing  | Analogue           | 12.5 / 20 / 25 kHz  |             |
|  | Digital            | 6.25 / 12.5 kHz   |             |
| Operating Voltage  |                    | 7.5V DC ± 20%   |             |
| Battery Life (5-5-90)  | KNB-55L (1480 mAh) | Approx. 8.5 hours   |             |
|  | KNB-56N (1400 mAh) | Approx. 8.5 hours   |             |
|  | KNB-57L (2000 mAh) | Approx. 11.5 hours  |             |
| Operating Temperature Range                                    |                    | -30° C to +60° C  |             |
| Frequency Stability  |                    | ± 2.0 ppm   | ± 1.0 ppm   |
| Antenna Impedance  |                    | 50 Ω  |             |
| Dimensions (W x H x D) <small>Projections not included</small> | LCD Models         | 56.0 x 110.5 x 36.9 mm (radio only)<br>56.0 x 110.5 x 37.5 mm (with KNB-55L)<br>56.0 x 110.5 x 39.5 mm (with KNB-57L) |             |
|  | Non LCD Models     | 56.0 x 110.5 x 37.5 mm (radio only)<br>56.0 x 110.5 x 38.1 mm (with KNB-55L)<br>56.0 x 110.5 x 40.1 mm (with KNB-57L) |             |
| Weight (net)   | LCD Models         | 210 g (radio only)<br>305 g (with KNB-55L)<br>330 g (with KNB-57L)  |             |
|  | Non LCD Models     | 205 g (radio only)<br>300 g (with KNB-55L)<br>330 g (with KNB-57L)  |             |
| Applicable Standards ETSI R & TTE                              |                    | EN 300 086, EN 300 113, EN 300 219, EN 310 489, EN 301 166  |             |
| Applicable Standards   |                    | EN 60065, EN 60950-1, EN 60215  |             |

|  |                 | NX-220  | NX-320 |
|--|-----------------|---|--------|
| <b>RECEIVER</b>  |                 |   |        |
| Sensitivity (Analogue)                                 | EIA 12 dB SINAD | 0.28 μV / 0.28 μV / 0.32 μV   |        |
| (25kHz / 20kHz / 12.5kHz)                              | EIA 20 dB SINAD | -3 dB μV (0.35 μV) / -3 dB μV (0.35 μV) / -1 dB μV (0.45 μV)  |        |
| Selectivity (Digital)                                  | 3% BER          | 0.32 μV / 0.25 μV   |        |
| (12.5kHz / 6.25kHz)                                    | 1% BER          | -1 dB μV (0.45 μV) / -4 dB μV (0.32 μV)   |        |
| Adjacent Channel Selectivity (25kHz / 20kHz / 12.5kHz) | (Analogue)      | 76 dB / 74 dB / 68 dB   |        |
| Intermodulation Distortion                             | (Analogue)      | 65 dB   |        |
| Spurious Response Rejection                            | (Analogue)      | 75 dB   |        |
| Audio Distortion                                       |                 | Less than 3%  |        |
| Audio Output   |                 | 500 mW / 8 Ω  |        |
| <b>TRANSMITTER</b>                                     |                 |   |        |
| RF Power Output  | High / Low      | 5 W / 1 W   |        |
| Modulation Limiting                                    | (Analogue)      | ± 5.0 kHz at 25 kHz<br>± 4.0 kHz at 20 kHz<br>± 2.5 kHz at 12.5 kHz   |        |
| Spurious Response                                      |                 | -36 dBm ≤ 1 GHz, -30 dBm > 1 GHz  |        |
| FM Hum & Noise (EIA)                                   |                 |   |        |
| (Analogue, 25 kHz / 20 kHz / 12.5 kHz)                 |                 | 45 dB / 45 dB / 40 dB   |        |
| Modulation Distortion                                  |                 | Less than 3%  |        |
| Microphone Impedance                                   |                 | 1.8 k Ω   |        |
| Modulation   |                 | 16K0F3E, 14K0F3E, 14K0F2D, 12K0F2D, 8K50F3E, 7K50F2D, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F7D, 4K00F7W, 4K00F2D |        |

Analogue measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation. FleetSync® is a registered trademark of JVCケンウッド Corporation. LTR® is a registered trademark of Transcript International. AMBE+2™ is a trademark of Digital Voice Systems Inc. Windows® is a registered trademark of Microsoft Corporation. NXDN® is a registered trademark of JVCケンウッド Corporation and Icom Inc. NEXEDGE® is a registered trademark of JVCケンウッド Corporation.

## Applicable MIL-STD & IP

| MIL Standard                             | MIL 810C<br>Methods/Procedures | MIL 810D<br>Methods/Procedures | MIL 810E<br>Methods/Procedures | MIL 810F<br>Methods/Procedures | MIL 810G<br>Methods/Procedures |
|--|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Low Pressure                             | 500.1/Procedure I              | 500.2/Procedure I, II          | 500.3/Procedure I, II          | 500.4/Procedure I, II          | 500.5/Procedure I, II          |
| High Temperature                         | 501.1/Procedure I, II          | 501.2/Procedure I, II          | 501.3/Procedure I, II          | 501.4/Procedure I, II          | 501.5/Procedure I, II          |
| Low Temperature                          | 502.1/Procedure I              | 502.2/Procedure I, II          | 502.3/Procedure I, II          | 502.4/Procedure I, II          | 502.5/Procedure I, II          |
| Temperature Shock                        | 503.1/Procedure I              | 503.2/Procedure I              | 503.3/Procedure I              | 503.4/Procedure I, II          | 503.5/Procedure I              |
| Solar Radiation                          | 505.1/Procedure I              | 505.2/Procedure I              | 505.3/Procedure I              | 505.4/Procedure I              | 505.5/Procedure I              |
| Rain                                     | 506.1/Procedure I, II          | 506.2/Procedure I, II          | 506.3/Procedure I, II          | 506.4/Procedure I, III         | 506.5/Procedure I, III         |
| Humidity                                 | 507.1/Procedure I, II          | 507.2/Procedure II, III        | 507.3/Procedure II, III        | 507.4                          | 507.5/Procedure II             |
| Salt Fog                                 | 509.1/Procedure I              | 509.2/Procedure I              | 509.3/Procedure I              | 509.4                          | 509.5                          |
| Dust                                     | 510.1/Procedure I              | 510.2/Procedure I              | 510.3/Procedure I              | 510.4/Procedure I, III         | 510.5/Procedure I              |
| Vibration                                | 514.2/Procedure VIII, X        | 514.3/Procedure I              | 514.4/Procedure I              | 514.5/Procedure I              | 514.6/Procedure I              |
| Shock                                    | 516.2/Procedure I, II, V       | 516.3/Procedure I, IV          | 516.4/Procedure I, IV          | 516.5/Procedure I, IV          | 516.6/Procedure I, IV          |
| <b>International Protection Standard</b> |                                |                                |                                |                                |                                |
| Dust & Water Protection                  | IP54/55                        |                                |                                |                                |                                |

\*To meet MIL810 and IP grade, the 2-pin connector has to be connected.

# KENWOOD

12 Priestley Way, London, NW2 7BA, United Kingdom  
www.kenwoodcommunications.co.uk



ISO9001 Registered  
Professional Systems Business Group  
JVCケンウッド Corporation

COMNX220E/320ECAT/2 Printed in UK